



Features

The Rack Busbar family is designed for data center server racks, compliant with Open Compute Project (OCP) specifications.

Specification

- Supports 48VDC to 54VDC for busbar interconnection.
- Rated current: 300A, 600A, and 1200A; 1400A is under development.
- Recommended height: 44OU to 48OU.
- Designed to follow OCP ORV3 48VDC busbar geometry, ensuring interoperability with different ratings of busbar connectors.
- Well-plated copper to ensure mating quality.

Headquarters

BizLink Technology, Inc.

47211 Bayside Parkway, Fremont, CA 94538, USA
Phone +1 510 252 0786 sales@bizlinktech.com
www.bizlinktech.com

Data center Solutions

| Inquiry datacenter_info@bizlinktech.com

© 2024 BizLink Confidential & Privileged

Global Sales Contacts

USA sales@bizlinktech.com
Europe sales_europe@bizlinktech.com
China sales_gc@bizlinktech.com
India sales_india@bizlinktech.com

Japan sales_japan@bizlinktech.com
Malaysia sales_malaysia@bizlinktech.com
Taiwan sales_tw@bizlinktech.com

BizLink and other trademarks are trademarks of BizLink Group or its subsidiaries. October 2023
Other trademarks may be trademarks of their respective owners. Specifications are subject to change without prior notice.

