



Wireless Charger

- Input: DC 9V - 16V
- Output: 5W/7.5W/10W/15W (Max.)
- Operating Temperature: -40°C to +85°C
- Protection: OCP/ OVP/ OTP/ SCP
- Compatible with Qi charging specifications
- Support FOD detection, LED indication and LIN/CAN Bus interface



USB Type-C® Charging Hub

- One USB Type-C Port : Support power delivery up to 100W
- Two USB Type-C Ports : Support power delivery up to 105W
- Input: DC 9V - 16V
- Operating Temperature: -40°C to +85°C
- Protection: OCP/ OVP/ OTP/ UTP/ SCP
- Support dust and water resistance

Headquarters

BizLink Technology, Inc.

47211 Bayside Parkway, Fremont, CA 94538, USA
Phone +1 510 252 0786 sales@bizlinktech.com

Global Sales Contacts

USA sales@bizlinktech.com
Europe sales@bizlinktech.com
China sales_gc@bizlinktech.com
India sales_india@bizlinktech.com

Japan sales_japan@bizlinktech.com
Malaysia sales_malaysia@bizlinktech.com
Taiwan sales_tw@bizlinktech.com

© 2023 BizLink Group. All rights reserved.

BizLink and other trademarks are trademarks of BizLink Group or its subsidiaries.

Other trademarks may be trademarks of their respective owners. Specifications are subject to change without prior notice.

November 2023

