

BizLink

TYPE CW3201

Plug for safety class I + II

2-pole plug with/without earthing-contact and fuse

BS 1363-1, SS 145-1


6 A/10 A/13 A, 250 V~

3 A/5 A/10 A/13 A

pins provided with insulating sleeves



Technical drawing



Approvals



Suitable flexible cord types

H03VVH2-F	2 x 0.75	H05VVH2-F	2 x 0.75
H05VVH2-F	2 x 1	H05V2V2H2-F	2 x 0.75
H05V2V2H2-F	2 x 1	H05VV-F	2 x 0.75
H05VV-F	2 x 1	H05VV-F	2 x 1.5
H05V2V2-F	2 x 0.75	H05V2V2-F	2 x 1
H05V2V2-F	2 x 1.5	H05RR-F	2 x 0.75
H05RR-F	2 x 1	H05RN-F	2 x 0.75
H05RN-F	2 x 1	H07RN-F	2 x 1
H07RN-F	2 x 1.5	H05BQ-F	2 x 1
H07BQ-F	2 x 1	H07BQ-F	2 x 1.5
H03VV-F	3 G 0.75	H03RT-F	3 G 0.75
H03RT-F	3 G 1	H05VV-F	3 G 0.75
H05VV-F	3 G 1	H05VV-F	3 G 1.5
H05V2V2-F	3 G 0.75	H05V2V2-F	3 G 1
H05V2V2-F	3 G 1.5	H05RR-F	3 G 0.75
H05RR-F	3 G 1	H05RN-F	3 G 0.75
H05RN-F	3 G 1	H07RN-F	3 G 1
H07RN-F	3 G 1.5	H05BQ-F	3 G 1
H07BQ-F	3 G 1	H07BQ-F	3 G 1.5
H03Z1Z1-F	2 x 0.75	H03Z1Z1-F	3 G 0.75

BizLink

TYPE CW3201

Suitable flexible cord types

H05Z1Z1-F	2 x 0.75	H05Z1Z1-F	2 x 1
H05Z1Z1-F	2 x 1.5	H05Z1Z1-F	3 G 0.75
H05Z1Z1-F	3 G 1	H05Z1Z1-F	3 G 1.5
H03Z1Z1H2-F	2 x 0.75	H05Z1Z1H2-F	2 x 0.75
H05Z1Z1H2-F	2 x 1	H03RT-H	3 G 0.75
H03RT-H	3 G 1		

Saudi-Arabia

H03VVH2-F	2 x 0.75	H05VV-F	2 x 0.75
H05VV-F	2 x 1	H05VV-F	2 x 1.5
H05VVH2-F	2 x 0.75	H05VVH2-F	2 x 1
H05V2V2-F	2 x 0.75	H05V2V2-F	2 x 1
H05V2V2-F	2 x 1.5	H05V2V2H2-F	2 x 0.75
H05V2V2H2-F	2 x 1	H05RR-F	2 x 0.75
H05RR-F	2 x 1	H05RN-F	2 x 0.75
H05RN-F	2 x 1	H07RN-F	2 x 1
H07RN-F	2 x 1.5	H05BQ-F	2 x 1
H07BQ-F	2 x 1	H07BQ-F	2 x 1.5
H03VV-F	3 G 0.75	H03V2V2-F	3 G 0.75
H05VV-F	3 G 0.75	H05VV-F	3 G 1
H05VV-F	3 G 1.5	H05V2V2-F	3 G 0.75
H05V2V2-F	3 G 1	H05V2V2-F	3 G 1.5
H03RT-H	3 G 0.75	H03RT-H	3 G 1
H05RR-F	3 G 0.75	H05RR-F	3 G 1
H05RN-F	3 G 0.75	H05RN-F	3 G 1
H07RN-F	3 G 1	H07RN-F	3 G 1.5
H05BQ-F	3 G 1	H07BQ-F	3 G 1
H07BQ-F	3 G 1.5		

Checked by Intertek.